

Centralized Logging Patterns

Philipp Krenn

@xeraa



@xeraa


```
java-logging — fish /Users/philipp/Documents/GitHub/java-logging — -fish — 105x26
[philipp@~/Documents/GitHub/java-logging(git*master)*> gradle run 14:47:14]

> Task :run
[2018-05-31 14:47:22.185] TRACE net.xeraa.logging.LogMe [main] - session=29, loop=1 - Iteration '1' and session '29'
[2018-05-31 14:47:22.196] DEBUG net.xeraa.logging.LogMe [main] - session=29, loop=1 - Collect in development
[2018-05-31 14:47:22.200] TRACE net.xeraa.logging.LogMe [main] - session=49, loop=2 - Iteration '2' and session '49'
[2018-05-31 14:47:22.201] DEBUG net.xeraa.logging.LogMe [main] - session=49, loop=2 - Collect in development
[2018-05-31 14:47:22.202] TRACE net.xeraa.logging.LogMe [main] - session=85, loop=3 - Iteration '3' and session '85'
[2018-05-31 14:47:22.203] INFO net.xeraa.logging.LogMe [main] - session=85, loop=3 - Collect in production
[2018-05-31 14:47:22.204] TRACE net.xeraa.logging.LogMe [main] - session=55, loop=4 - Iteration '4' and session '55'
[2018-05-31 14:47:22.204] DEBUG net.xeraa.logging.LogMe [main] - session=55, loop=4 - Collect in development
[2018-05-31 14:47:22.205] TRACE net.xeraa.logging.LogMe [main] - session=83, loop=5 - Iteration '5' and session '83'
[2018-05-31 14:47:22.205] WARN net.xeraa.logging.LogMe [main] - session=83, loop=5 - Investigate tomorrow
[2018-05-31 14:47:22.206] TRACE net.xeraa.logging.LogMe [main] - session=36, loop=6 - Iteration '6' and session '36'
[2018-05-31 14:47:22.206] INFO net.xeraa.logging.LogMe [main] - session=36, loop=6 - Collect in production
```


```
java-logging — fish /Users/philipp/Documents/GitHub/java-logging — -fish — 105x26
[philipp@~/Documents/GitHub/java-logging(git*master)✓] cat logs/java-logging.log 14:47:23
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and session '46'
[2018-05-31 14:42:58.961] DEBUG net.xeraa.logging.LogMe [main] - session=46, loop=1 - Collect in development
[2018-05-31 14:42:58.963] TRACE net.xeraa.logging.LogMe [main] - session=13, loop=2 - Iteration '2' and session '13'
[2018-05-31 14:42:58.963] DEBUG net.xeraa.logging.LogMe [main] - session=13, loop=2 - Collect in development
[2018-05-31 14:42:58.964] TRACE net.xeraa.logging.LogMe [main] - session=70, loop=3 - Iteration '3' and session '70'
[2018-05-31 14:42:58.964] INFO net.xeraa.logging.LogMe [main] - session=70, loop=3 - Collect in production
[2018-05-31 14:42:58.965] TRACE net.xeraa.logging.LogMe [main] - session=68, loop=4 - Iteration '4' and session '68'
[2018-05-31 14:42:58.966] DEBUG net.xeraa.logging.LogMe [main] - session=68, loop=4 - Collect in development
[2018-05-31 14:42:58.966] TRACE net.xeraa.logging.LogMe [main] - session=84, loop=5 - Iteration '5' and session '84'
[2018-05-31 14:42:58.966] WARN net.xeraa.logging.LogMe [main] - session=84, loop=5 - Investigate tomorrow
[2018-05-31 14:42:58.967] TRACE net.xeraa.logging.LogMe [main] - session=82, loop=6 - Iteration '6' and session '82'
[2018-05-31 14:42:58.969] INFO net.xeraa.logging.LogMe [main] - session=82, loop=6 - Collect in production
[2018-05-31 14:42:58.969] TRACE net.xeraa.logging.LogMe [main] - session=7, loop=7 - Iteration '7' and se
```



```
java-logging — tail /Users/philipp/Documents/GitHub/java-logging — tail -f logs/java-loggi...
[philipp@~/Documents/GitHub/java-logging(git*master)✓> tail -f logs/java-logging.log 18:39:45]
[2018-05-31 17:20:22.874] TRACE net.xeraa.logging.LogMe [main] - session=61, loop=16 - Iteration '16' and
session '61'
[2018-05-31 17:20:22.874] DEBUG net.xeraa.logging.LogMe [main] - session=61, loop=16 - Collect in develop
ment
[2018-05-31 17:20:22.881] TRACE net.xeraa.logging.LogMe [main] - session=2, loop=17 - Iteration '17' and
session '2'
[2018-05-31 17:20:22.882] DEBUG net.xeraa.logging.LogMe [main] - session=2, loop=17 - Collect in developm
ent
[2018-05-31 17:20:22.883] TRACE net.xeraa.logging.LogMe [main] - session=35, loop=18 - Iteration '18' and
session '35'
[2018-05-31 17:20:22.884] INFO net.xeraa.logging.LogMe [main] - session=35, loop=18 - Collect in product
ion
[2018-05-31 17:20:22.886] TRACE net.xeraa.logging.LogMe [main] - session=86, loop=19 - Iteration '19' and
session '86'
[2018-05-31 17:20:22.889] DEBUG net.xeraa.logging.LogMe [main] - session=86, loop=19 - Collect in develop
ment
[2018-05-31 17:20:22.890] TRACE net.xeraa.logging.LogMe [main] - session=92, loop=20 - Iteration '20' and
session '92'
[2018-05-31 17:20:22.891] WARN net.xeraa.logging.LogMe [main] - session=92, loop=20 - Investigate tomorr
OW
[2018-05-31 18:40:05.399] TRACE net.xeraa.logging.LogMe [main] - session=40, loop=1 - Iteration '1' and s
ession '40'
[2018-05-31 18:40:05.417] DEBUG net.xeraa.logging.LogMe [main] - session=40, loop=1 - Collect in developm
ent
[2018-05-31 18:40:05.420] TRACE net.xeraa.logging.LogMe [main] - session=51, loop=2 - Iteration '2' and s
```



```
java-logging — fish /Users/philipp/Documents/GitHub/java-logging — -fish — 105x26
philipp@~/Documents/GitHub/java-logging(git*master)➤ less +F logs/java-logging.log 18:42:08
```



java-logging — fish /Users/philipp/Documents/GitHub/java-logging — -fish — 105x12

```
[cat logs/java-logging.log]
```

```
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and session '46'
```

```
[2018-05-31 14:42:58.961] DEBUG net.xeraa.logging.LogMe [main] - session=46, loop=1 - Collect in development
```

```
[2018-05-31 14:42:58.963] TRACE net.xeraa.logging.LogMe [main] - session=13, loop=2 - Iteration '2' and s
```

```
[cat logs/java-logging.log]
```

```
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and session '46'
```

```
[2018-05-31 14:42:58.961] DEBUG net.xeraa.logging.LogMe [main] - session=46, loop=1 - Collect in development
```

```
[2018-05-31 14:42:58.963] TRACE net.xeraa.logging.LogMe [main] - session=13, loop=2 - Iteration '2' and s
```

```
[cat logs/java-logging.log]
```

```
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and session '46'
```

```
[2018-05-31 14:42:58.961] DEBUG net.xeraa.logging.LogMe [main] - session=46, loop=1 - Collect in development
```

```
[2018-05-31 14:42:58.963] TRACE net.xeraa.logging.LogMe [main] - session=13, loop=2 - Iteration '2' and session '13'
```

```
[2018-05-31 14:42:58.963] DEBUG net.xeraa.logging.LogMe [main] - session=13, loop=2 - Collect in development
```

```
[2018-05-31 14:42:58.964] TRACE net.xeraa.logging.LogMe [main] - session=70, loop=3 - Iteration '3' and session '70'
```

```
[2018-05-31 14:42:58.964] INFO net.xeraa.logging.LogMe [main] - session=70, loop=3 - Collect in producti
```

```
java-logging — fish /Users/philipp/Documents/GitHub/java-logging — -fish — 105x1
[cat logs/java-logging.log]
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and s

[cat logs/java-logging.log]
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and s

[cat logs/java-logging.log]
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and s

[cat logs/java-logging.log]
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and s

[cat logs/java-logging.log]
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and s

[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and s
session '46'

[cat logs/java-logging.log]
[2018-05-31 14:42:58.951] TRACE net.xeraa.logging.LogMe [main] - session=46, loop=1 - Iteration '1' and s

[cat logs/java-logging.log]
```


The background image shows a large, rusted metal structure, likely the hull of a ship, with various pipes and mechanical components visible. A bright light source, possibly a searchlight or a flare, is visible in the upper right background, casting a glow. The overall scene is somewhat dark and industrial.

me looking
for the bug

7.2 GB
of log file




ALL THE THINGS!





elastic

Developer 🥑



E Elasticsearch

L Logstash

K Kibana




slack



fitbit


*Apparently, I'm an
ELKB personality.*







elastic stack



Disclaimer

I build **highly** monitored Hello World
apps

Example: Java

SLF4J, Logback, MDC with logstash-logback-encoder

Alternative <https://github.com/vy/log4j2-logstash-layout>

And Everywhere Else

.NET: NLog

JavaScript: Winston

Python: structlog

PHP: Monolog


Anti-Pattern: `print`

```
System.out.println("Oops");
```

Anti-Pattern: Coupling

Parse





Bind Mount Logs

```
java_app:  
  volumes:  
    - './logs-docker/:/logs/'  
  ...  
  
filebeat_for_logstash:  
  volumes:  
    - './logs-docker/:/mnt/logs/:ro'  
  ...
```

Collect Log Lines

```
filebeat.inputs:  
- type: log  
  paths:  
    - /mnt/logs/*.log
```

Metadata

processors:

- add_host_metadata: ~

Setting for negate	Setting for match	Result	Example pattern: ^b
false	after	Consecutive lines that match the pattern are appended to the previous line that doesn't match.	
false	before	Consecutive lines that match the pattern are prepended to the next line that doesn't match.	
true	after	Consecutive lines that don't match the pattern are appended to the previous line that does match.	
true	before	Consecutive lines that don't match the pattern are prepended to the next line that does match.	

Test Multiline Pattern

https://www.elastic.co/guide/en/beats/filebeat/current/_test_your_regexp_pattern_for_multiline.html

```
The Go Playground  Run Format Imports Share

1 package main
2 |
3 import (
4     "fmt"
5     "regexp"
6     "strings"
7 )
8
9 var pattern = `^\[`
10 var negate = true
11
12 var content = `[2019-05-21 09:35:52.004] ERROR net.xeraa.logging.LogMe [main] - user_experience=0.0,
13 java.lang.RuntimeException: Bad runtime...
14     at net.xeraa.logging.LogMe.main(LogMe.java:30)
15 [2019-05-21 09:35:52.006] TRACE net.xeraa.logging.LogMe [main] - session=59, loop=16 - It
16 [2019-05-21 09:35:52.007] DEBUG net.xeraa.logging.LogMe [main] - session=59, loop=16 - Co
17 `
18
19 func main() {
20     regex, err := regexp.Compile(pattern)
21     if err != nil {
22         fmt.Println("Failed to compile pattern: ", err)
23     }
24 }

matches line
false [2019-05-21 09:35:52.004] ERROR net.xeraa.logging.LogMe [main] - user_experience=0.0,
true  java.lang.RuntimeException: Bad runtime...
true    at net.xeraa.logging.LogMe.main(LogMe.java:30)
false [2019-05-21 09:35:52.006] TRACE net.xeraa.logging.LogMe [main] - session=59, loop=16
false [2019-05-21 09:35:52.007] DEBUG net.xeraa.logging.LogMe [main] - session=59, loop=16
true
```

Grok

<https://github.com/logstash-plugins/logstash-patterns-core/blob/master/patterns/grok-patterns>

96 lines (85 sloc)	5.21 KB
--------------------	---------

```

1  USERNAME [a-zA-Z0-9._-]+
2  USER %{USERNAME}
3  EMAILLOCALPART [a-zA-Z][a-zA-Z0-9_+.=:]+
4  EMAILADDRESS %{EMAILLOCALPART}@%{HOSTNAME}
5  INT (?:[+-]?(?:[0-9]+))
6  BASE10NUM (?![0-9._+])(?>[+-]?(?:?:[0-9]+(?:?:\.[0-9]+)?|(?:?:\.[0-9]+)))
7  NUMBER (?:%{BASE10NUM})
8  BASE16NUM (?![0-9A-Fa-f])(?:[+-]?(?:?:0x)?(?:?:[0-9A-Fa-f]+))
9  BASE16FLOAT \b(?![0-9A-Fa-f.])(?:[+-]?(?:?:0x)?(?:?:[0-9A-Fa-f]+(?:?:\.[0-9A-Fa-f]*)?)|(?
10
11  POSINT \b(?:[1-9][0-9]*)\b
12  NONNEGINT \b(?:[0-9]+)\b
13  WORD \b\w+\b
14  NOTSPACE \S+
15  SPACE \s*
16  DATA .*?
17  GREEDYDATA .*
18  QUOTEDSTRING (?>(?!\\)(?>"(?>\\.|^[^"])+)"|'(?>'(?>\\.|^[^']+)+')|'|(?>`(?>\\.|^[^`]+)`))
19  UUID [A-Fa-f0-9]{8}-(?:[A-Fa-f0-9]{4}-){3}[A-Fa-f0-9]{12}
20  # URN, allowing use of RFC 2141 section 2.3 reserved characters
21  URN urn:[0-9A-Za-z][0-9A-Za-z-]{0,31}:(?:%[0-9a-fA-F]{2}|[0-9A-Za-z()+,.;=@;$_!*'/?#-])
22
23  # Networking
24  MAC (?:%{CISCOMAC}|%{WINDOWSMAC}|%{COMMONMAC})
25  CISCOMAC (?:?:[A-Fa-f0-9]{4}\.){2}[A-Fa-f0-9]{4}
26  WINDOWSMAC (?:?:[A-Fa-f0-9]{2}-){5}[A-Fa-f0-9]{2})

```

Dev Tools

Grok Debugger

Sample Data

```
1 [2018-11-16 01:16:59.983] ERROR net.xeraa.logging.LogMe [main] - user_experience=👎, ses
```

Grok Pattern

```
1 \[%{TIMESTAMP_ISO8601:timestamp}\] %{LOGLEVEL:loglevel}
```

> Custom Patterns

[Simulate](#)

Structured Data

```
1 {  
2   "loglevel": "ERROR",  
3   "timestamp": "2018-11-16 01:16:59.983"  
4 }
```



```
[2018-09-28 10:30:38.516] ERROR net.xeraa.logging.LogMe [main] -  
    user_experience=🤔, session=46, loop=15 -  
    Wake me up at night  
java.lang.RuntimeException: Bad runtime...  
    at net.xeraa.logging.LogMe.main(LogMe.java:30)
```

```
^\[%{TIMESTAMP_ISO8601:@timestamp}\] %{SPACE} %{LOGLEVEL:log.level}  
%{SPACE} %{USERNAME:log.package} %{SPACE} \[%{WORD:log.method}\]  
%{SPACE} - %{SPACE} %{GREEDYDATA:log.labels} %{SPACE} - %{SPACE}  
%{GREEDYDATA:message} (?: \n+ (?<stacktrace> (?: . | \r | \n) + ) ) ?
```

Elastic Common Schema

<https://github.com/elastic/ecs>

Event fields

The event fields are used for context information about the data itself.

Field	Description	Level	Type	Example
event.id	Unique ID to describe the event.	core	keyword	8a4f500d
event.category	Event category. This can be a user defined category.	core	keyword	metrics
event.type	A type given to this kind of event which can be used for grouping. This is normally defined by the user.	core	keyword	nginx-stats-metrics
event.action	The action captured by the event. The type of action will vary from system to system but is likely to include actions by security services, such as blocking or quarantining; as well as more generic actions such as login	core	keyword	reject



@xeraa

Machine Learning Data Visualizer


```
28 [2018-11-16 01:16:59.976] DEBUG net.xeraa.logging.LogMe [main] - session=94, loop=14 - Collect
29 [2018-11-16 01:16:59.977] TRACE net.xeraa.logging.LogMe [main] - session=43, loop=15 - Iteration
30 [2018-11-16 01:16:59.983] ERROR net.xeraa.logging.LogMe [main] - user_experience=😞, session=43
31 java.lang.RuntimeException: Bad runtime...
```

Summary

Number of lines analyzed	293
Format	semi_structured_text
Grok pattern	\[%{TIMESTAMP_ISO8601:timestamp}\] %{LOGLEVEL:loglevel} .*? .*?\[.*?\] .*? .*?\bssess
Time field	timestamp
Time format	YYYY-MM-dd HH:mm:ss.SSS

[Override settings](#)

File stats



Logstash Key Value Filter for MDC


```
kv {  
  source => "labels"  
  field_split => ","  
  trim_key => " "  
}
```

Pro: No change

Con: Regular expression, multiline,
format changes

Send





logback.xml


```
<appender name="logstash" class="net.logstash.logback.appender.LogstashAccessTcpSocketAppender">  
  <destination>logstash:4560</destination>  
  <encoder class="net.logstash.logback.encoder.LogstashEncoder"/>  
</appender>
```

Pro: No files

Con: Outages & coupling

Structure





Collect JSON

```
filebeat.input:  
- type: log  
  paths:  
    - /mnt/logs/*.json  
  json:  
    message_key: message  
    keys_under_root: true
```

Stack(trace) Hash

Bonues: Multi-Index


```
output.elasticsearch:  
  hosts: ["http://localhost:9200"]  
  indices:  
    - index: "warning-%{[agent.version]}-%{+yyyy.MM.dd}"  
      when.contains:  
        message: "WARN"  
    - index: "error-%{[agent.version]}-%{+yyyy.MM.dd}"  
      when.contains:  
        message: "ERR"
```

Pro: Right format

Con: JSON serialization overhead

Containerize






docker

Where to put Filebeat?

Sidecar



[https://github.com/elastic/beats/tree/
master/deploy/docker](https://github.com/elastic/beats/tree/master/deploy/docker)

Docker Logs

```
filebeat.autodiscover:
```

```
  providers:
```

```
    - type: docker
```

```
      hints.enabled: true
```

```
processors:
```

```
  - add_docker_metadata: ~
```

Metadata

No Docker metadata with the other methods


```
"docker": {
  "container": {
    "labels": {
      "app": "fizzbuzz",
      "co_elastic_logs/multiline_match": "after",
      "com_docker_compose_config-hash": "41520c6cf2b6a1f3dae4f16d0a6fd76760cdfc38fbfe43a3a3be2e09bdd1b8b5",
      "environment": "production",
      "co_elastic_logs/multiline_pattern": "^\\\[",
      "co_elastic_logs/multiline_negate": "true",
      "com_docker_compose_oneoff": "False",
      "com_docker_compose_project": "java-logging",
      "com_docker_compose_service": "java_app",
      "com_docker_compose_container-number": "1",
      "com_docker_compose_version": "1.23.2"
    }
  }
}
```

Missing the Last Line

Waiting for the newline

Hints

labels:

- "app=fizzbuzz"
- "co.elastic.logs/multiline.pattern=^\\\\"
- "co.elastic.logs/multiline.negate=true"
- "co.elastic.logs/multiline.match=after"

Registry File

`filebeat.registry.path: /usr/share/filebeat/data/registry`

Ingest Pipeline

```
output.elasticsearch:  
  hosts: ["http://elasticsearch:9200"]  
  index: "docker"  
  pipelines:  
    - pipeline: "parse_java"  
      when.contains:  
        container.name: "java_app"
```


Ingest Pipeline

```
{
  "description" : "Parse Java log lines",
  "processors": [
    {
      "grok": {
        "field": "message",
        "patterns": [ "^\\[%{TIMESTAMP_ISO8601:timestamp}\\]%{SPACE}%{LOGLEVEL:log.level}%{SPACE}%{USERNAME:log.package}%{SPACE}\\[%{WORD:log.method}\\]%{SPACE}%{SPACE}%{GREEDYDATA:labels}%{SPACE}-%{SPACE}%{GREEDYDATA:message_parsed}(?:\\n+(?<stacktrace>(?:.|\\r|\\n)+))?" ],
        "ignore_failure": true
      }
    }
  ]
}
```


Unknown Fields

? log.labels	⚠ session=69, loop=20
t log.level	WARN
? log.method	⚠ main
# log.offset	19,744
? log.package	⚠ net.xeraa.logging.LogMe
t message	[2019-05-21 05:02:07.458] WARN net.xeraa.logging.LogMe [main] - session=69, loop=20 - Investigate tomorrow
? message_parsed	⚠ Investigate tomorrow
t stream	stdout
🕒 suricata.eve.timestamp	May 21, 2019 @ 07:02:07.459
? timestamp	⚠ 2019-05-21 05:02:07.458

ASCII Art



Redis 4.0.9 (00000000/0) 64 bit

Running in stand alone mode

Port: 6379

PID: 55757

<http://redis.io>

Configuration Templates

```
filebeat.autodiscover:  
  providers:  
    - type: docker  
      templates:  
        - condition:  
            equals:  
              docker.container.image: redis  
  config:  
    - type: docker  
      containers.ids:  
        - "${data.docker.container.id}"  
      exclude_lines: ["^\\s+[[\\-`('.|_]]"]
```

Who Logs the Logger

Avoid loops

Process without -e

```
filebeat.yml: logging.to_files: true
```

Pro: Hot 🍌

Con: Complexity

Orchestrate





kubernetes

Where to put Filebeat?

DaemonSet

[https://github.com/elastic/beats/tree/
master/deploy/kubernetes](https://github.com/elastic/beats/tree/master/deploy/kubernetes)

Metadata

Either in cluster or outside

processors:

- add_kubernetes_metadata:
in_cluster: true
- add_kubernetes_metadata:
in_cluster: false
host: <hostname>
kube_config: \${HOME}/.kube/config

```
{
  "host": "172.17.0.21",
  "port": 9090,
  "kubernetes": {
    "container": {
      "id": "382184ecdb385cfd5d1f1a65f78911054c8511ae009635300ac28b4fc357ce51",
      "image": "my-java:1.0.0",
      "name": "my-java"
    },
    "labels": {
      "app": "java",
    },
    "namespace": "default",
    "node": {
      "name": "minikube"
    },
    "pod": {
      "name": "java-2657348378-k1pnh"
    }
  },
}
```

More Metadata

Add: Cloud, local timezone, process

Drop: Events, fields

Rename: Fields

Dissect, DNS reverse lookup

Configuration Templates

```
filebeat.autodiscover:  
  providers:  
    - type: kubernetes  
      templates:  
        - condition:  
            equals:  
              kubernetes.namespace: redis  
  config:  
    - type: docker  
      containers.ids:  
        - "${data.kubernetes.container.id}"  
  exclude_lines: ["^\\s+[\\-`('.|_]"
```

Customize Indices

```
output.elasticsearch:
```

```
  index: "%{[kubernetes.namespace]:filebeat}-%{[beat.version]}-%{+yyyy.MM.dd}"
```


Pro: Hot 🍌🍌🍌

Con: Complexity++

Conclusion

Examples

<https://github.com/xeraa/java-logging>

Parse 

Send 

Structure 

Containerize 

Orchestrate 

Questions?

Philipp Krenn

@xeraa