

The Art
of the AGT



JS



// TODO

Write linting rules to enforce your team's code conventions



Write your own javascript transpiling code



Write powerful "code-mods" to automatically refactor thousands of legacy scripts from ES5 to ES6

jscodeshift

ESTree-based AST

+

Visitor Pattern

Webpack

Babel

Uglifyjs



Rollup

ESLint

Istanbul

Ternjs

jscodeshift




BABEL R_o



Abstract
Syntax
Tree

```
var foo = 'bar';
```



```
var foo = 'bar'; {
  "type": "Program",
  "body": [
    {
      "type": "VariableDeclaration",
      "declarations": [
        {
          "type": "VariableDeclarator",
          "id": {
            "type": "Identifier",
            "name": "foo"
          },
          "init": {
            "type": "Literal",
            "value": "bar"
          }
        }
      ],
      "kind": "var"
    }
  ]
}
```

I/ { Parse
Traverse

O { Manipulate
Generate code

W/ { Parse

O {

```
1 /**
2  * Paste or drop some JavaScript here and explore
3  * the syntax tree created by chosen parser.
4  * You can use all the cool new features from ES6
5  * and even more. Enjoy!
6  */
7
8 let tips = [
9   "Click on any AST node with a '+' to expand it",
10
11  "Hovering over a node highlights the \
12   corresponding part in the source code",
13
14  "Shift click on an AST node expands the whole substr
15 ];
16
17 function printTips() {
18   tips.forEach((tip, i) => console.log(`Tip ${i}:` + t
19 }
20
```

Autofocus Hide methods Hide empty keys Hide local data

```
- Program {
  type: "Program"
  start: 0
  end: 476
  + range: [2 elements]
  - body: [
    + VariableDeclaration {type, start, end, range,
      declarations, ... +1}
    + FunctionDeclaration {type, start, end, range,
      ... +4}
  ]
  sourceType: "module"
}
```

astexplorer.net

W { Traverse

O {



piggy·back *(verb)*

piggy·back *(verb)*




piggy·back *(verb)*



piggy·back *(verb)*

window.Acme



ESLint rule

This code is a simplified version of the `eslint-plugin-piggyback` plugin:
<https://github.com/cowchimp/eslint-plugin-piggyback>

```
1. module.exports = function(context) {
2.   var globalScope;
3.
4.   return {
5.     "MemberExpression": function(node) {
6.       if(
7.         node.object.type === "Identifier" &&
8.         node.object.name === "window" &&
9.         !isValidGlobalProperty(node.property.name)
10.      ) {
```

```
1. module.exports = function(context) {
2.   var globalScope;
3.
4.   return {
5.     "MemberExpression": function(node) {
6.       if(
7.         node.object.type === "Identifier" &&
8.         node.object.name === "window" &&
9.         !isValidGlobalProperty(node.property.name)
10.      ) {
11.        context.report(
```

Visit all `{{foo}}.{{bar}}` nodes

```
14.         `${node.object.name} global scope`,
```

```
1. module.exports = function(context) {
2.   var globalScope;
3.
4.   return {
5.     "MemberExpression": function(node) {
6.       if(
7.         node.object.type === "Identifier" &&
8.         node.object.name === "window" &&
9.         !isValidGlobalProperty(node.property.name)
10.      ) {
11.        context.report(
12.          node,
13.          `${node.property.name} piggybacks on the
14.          ${node.object.name} global scope`,
15.          );

```

Check if it's a naughty node

```
3.
4.   return {
5.     "MemberExpression": function(node) {
6.       if(
7.         node.object.type === "Identifier" &&
8.         node.object.name === "window" &&
9.         !isValidGlobalProperty(node.property.name)
10.      ) {
11.        context.report(
12.          node,
13.          ` ${node.property.name} piggybacks on the
14.            ${node.object.name} global scope `,
15.        );
16.      }
17.    },
18.
19.    "Program": function() {
```

Report the violation

```
22.   };
```



```
14.         `${node.object.name} global scope`,
15.     );
16. }
17. },
18.
19.     "Program": function() {
20.         globalScope = context.getScope();
21.     }
22. };
23.
24. function isValidGlobalProperty(propertyName) {
25.     return globalScope.variables.some(
26.         v => v.name == propertyName
27.     );
28. }
29. };
```

Querying scope

VISITOR

I/ }

O { Manipulate

BABEL

Babel plugin

```
1. // Babel babel-plugin-transform-remove-debugger
2. // Author: Sebastian McKenzie
3. // License: MIT
4. // Url: https://github.com/babel
5.
6. export default function () {
7.   return {
8.     visitor: {
9.       "DebuggerStatement": function(path) {
10.        path.remove();
11.      }
12.    }
13.  }
```

```
1. // Babel babel-plugin-transform-remove-debugger
2. // Author: Sebastian McKenzie
3. // License: MIT
4. // Url: https://github.com/babel
5.
6. export default function () {
7.   return {
8.     visitor: {
9.       "DebuggerStatement": function(path) {
10.        path.remove();
11.      }
12.    }
13.  };
14. }
```

Find any `debugger` statement nodes

```
1. // Babel babel-plugin-transform-remove-debugger
2. // Author: Sebastian McKenzie
3. // License: MIT
4. // Url: https://github.com/babel
5.
6. export default function () {
7.   return {
8.     visitor: {
9.       "DebuggerStatement": function(path) {
10.        path.remove();
11.      }
12.    }
13.  };
14. }
```

Remove the node from the AST

W/ {

O { Generate code

jscodeshift

jscodeshift transform

```
1. module.exports = function(file, api) {
2.   var j = api.jscodeshift;
3.   var root = j(file.source);
4.
5.   root.find(j.VariableDeclaration, { kind: 'var' })
6.     .forEach(function(p) {
7.       var letStatement = j.variableDeclaration(
8.         'let',
9.         p.value.declarations
10.      );
```

```
1. module.exports = function(file, api) {  
2.   var j = api.jscodeshift;  
3.   var root = j(file.source);  
4.  
5.   root.find(j.VariableDeclaration, { kind: 'var' })  
6.     .forEach(function(p) {  
7.       var letStatement = j.variableDeclaration(  
8.         'let',  
9.         p.value.declarations  
10.      );
```

Convert the source code to an AST

```
1. module.exports = function(file, api) {
2.   var j = api.jscodeshift;
3.   var root = j(file.source);
4.
5.   root.find(j.VariableDeclaration, { kind: 'var' })
6.     .forEach(function(p) {
7.       var letStatement = j.variableDeclaration(
8.         'let',
9.         p.value.declarations
10.      );
11.      return j(p).replaceWith(letStatement);
12.    });
```

Find all `var` declaration nodes

```
1. module.exports = function(file, api) {
2.   var j = api.jscodeshift;
3.   var root = j(file.source);
4.
5.   root.find(j.VariableDeclaration, { kind: 'var' })
6.     .forEach(function(p) {
7.       var letStatement = j.variableDeclaration(
8.         'let',
9.         p.value.declarations
10.      );
11.      return j(p).replaceWith(letStatement);
12.    });
13.
```

...and for each one...

```
1. module.exports = function(file, api) {
2.   var j = api.jscodeshift;
3.   var root = j(file.source);
4.
5.   root.find(j.VariableDeclaration, { kind: 'var' })
6.     .forEach(function(p) {
7.       var letStatement = j.variableDeclaration(
8.         'let',
9.         p.value.declarations
10.      );
11.      return j(p).replaceWith(letStatement);
12.    });
13.
14.   return root.toSource();
15. };
```

Create a copy node but make it a `let` declaration

```
2.   var j = api.jscodeshift;
3.   var root = j(file.source);
4.
5.   root.find(j.VariableDeclaration, { kind: 'var' })
6.     .forEach(function(p) {
7.       var letStatement = j.variableDeclaration(
8.         'let',
9.         p.value.declarations
10.      );
11.      return j(p).replaceWith(letStatement);
12.    });
13.
14.   return root.toSource();
15. };
```

Replace the original node with the new one

```
4.  
5.   root.find(j.VariableDeclaration, { kind: 'var'  
6.     .forEach(function(p) {  
7.       var letStatement = j.variableDeclaration(  
8.         'let',  
9.         p.value.declarations  
10.      });  
11.      return j(p).replaceWith(letStatement);  
12.    });  
13.  
14.   return root.toSource();  
15. };
```

Convert the AST back into source code



BKcore / HexGL

Watch

81

★ Star

805

Fork

347

<> Code

🔔 Issues 10

🔀 Pull requests 0

📁 Projects 0

Insights ▾

Its 2017. Use Let instead of Var #40

New issue

🔔 Open

mainanick opened this issue on Dec 31, 2016 0 comments



mainanick commented on Dec 31, 2016

No description provided.

Assignees

No one assigned

Labels

None yet

Projects

None yet

Milestone

No milestone

1 participant



 github.com/cowchimp/awesome-ast

 [@cowchimp](https://twitter.com/cowchimp)

 blog.cowchimp.com