



Intro





main

elasticsearch / server / src / main / java / org / elasticsearch / rest / action / search / RestSearchAction.java



Code

Blame



Raw




```
56 public class RestSearchAction extends BaseRestHandler {
57     public List<Route> routes() {
58         return List.of(
59             new Route(GET, "/_search"),
60             new Route(POST, "/_search"),
61             new Route(GET, "{index}/_search"),
62             new Route(POST, "{index}/_search")
63         );
64     }
65
66     @Override
67     public Set<String> supportedCapabilities() {
68         return SearchCapabilities.CAPABILITIES;
69     }
70
71     @Override
72     public RestChannelConsumer prepareRequest(final RestRequest request, final NodeClient client) throws IOException
73     {
74         if (client.threadPool() != null && client.threadPool().getThreadContext() != null) {
75             client.threadPool().getThreadContext().setErrorTraceTransportHeader(request);
76         }
77         SearchRequest searchRequest = new SearchRequest();
78         // access the BwC param, but just drop it
```



Test coverage

```
»
743 9417 public IndexWriter(Directory d, In
744 9417     conf.setIndexWriter(this); // pr
745 9416     config = conf;
746 9416     directory = d;
747 9416     analyzer = config.getAnalyzer();
748 9416     infoStream = config.getInfoStrea
749 9416     mergeScheduler = config.getMerge
750 9416     codec = config.getCodec();
751
752 9416     bufferedUpdatesStream = new Buff
753 9416     poolReaders = config.getReaderPo
754
755 9416     writeLock = directory.makeLock(W
756
757 9414     if (!writeLock.obtain(config.get
758 0     throw new LockObtainFailedExce
759
760 9414     boolean success = false;
761 9414     try {
762 9414         OpenMode mode = config.getOpen
763 9414         boolean create;
764 9414         if (mode == OpenMode.CREATE) {
765 1963             create = true;
766 7451         } else if (mode == OpenMode.AP
767 802             create = false;
768         } else {
```





<https://plugins.jetbrains.com/plugin/3146-infinittest>

Run  RandomizedTest x



✓	✓	Rand	k.randomizedtesti	47 ms
	✓	randomIntegerWithSeed03		23 ms
	⊘	ignoreIfUseless20		5 ms
	✓	randomInteger02		1 ms
	✓	random00		1 ms
	✓	stopOrIdentifyYourThreads30		1 ms
	✓	randomLocale10		9 ms
>	✓	randomIntegerWithRange04		6 ms
	✓	randomWithSeed01		1 ms

Rerun Automatically

Actions

New workflow

All workflows



Configure for .asciidoc chang...

Documentation

Docs

docs-build

docs-cleanup

updatecli-compose

Validate Gradle Wrapper

Management

Caches

Deployments

Attestations

Runners

Usage metrics

Performance metrics

Validate Gradle Wrapper #59459: Commit [65e2c3f](#) pushed by [davidkyle](#)

8.19

2 weeks ago 27s

✔ **Remove index refresh block ITs (replaced by ITs i...**

Validate Gradle Wrapper #59458: Commit [650ce32](#) pushed by [benchaplin](#)

main

2 weeks ago 27s

✔ **Mute org.elasticsearch.index.mapper.vectors.De...**

Validate Gradle Wrapper #59457: Commit [0b0f4f8](#) pushed by [elasticsearchmachine](#)

main

2 weeks ago 24s

✔ **Mute org.elasticsearch.index.mapper.vectors.De...**

Validate Gradle Wrapper #59456: Commit [6af55c2](#) pushed by [elasticsearchmachine](#)

main

2 weeks ago 1m 1s

✔ **[ES|QL] Implement new syntax for RERANK and ...**

Validate Gradle Wrapper #59455: Commit [d56a476](#) pushed by [afoucret](#)

main

2 weeks ago 36s

✘ **Add test**

Validate Gradle Wrapper #59454: Commit [9e75c14](#) pushed by [felixbarny](#)

metrics_prototype

2 weeks ago 29s

✔ **Upgrade MinIO (& work around bug) (#132178)**

Validate Gradle Wrapper #59453: Commit [3a285cf](#) pushed by [elasticsearchmachine](#)

8.18

2 weeks ago 28s



Push code to production


- June 4th 1996
- Original footage from ESA



https://www.esa.int/ESA_Multimedia/Videos/1996/06/Ariane_501_recording_launch_pad_before_and_at_launch

```
public static int generateInteger(int min, int max) {  
    return ThreadLocalRandom.current().nextInt(min, max);  
}
```

```
@Test  
public void testInteger() {  
    int input = generateInteger(  
        Integer.MIN_VALUE,  
        Integer.MAX_VALUE);  
    int output = Math.abs(input);  
    assertThat(output, greaterThanOrEqualTo(0));  
}
```




```
Results Logging
fr.pilato.demo.testframework.IntegerTest:37 - AssertionError( Expected: a value equal to or greater than <0> but: <-2147483648> was less than <0>)

( Expected: a value equal to or greater than <0>
but: <-2147483648> was less than <0>)
```


Ran 0 Tests - Failures Detected

```
int output = Math.abs(input);
assertThat(output, greaterThanOrEqualTo(0));
```



Randomized Testing

Gotta Catch 'em all!



About Me



David Pilato

Developer | Evangelist





 [linkedin.com/in/dadoonet/](https://www.linkedin.com/in/dadoonet/)

 [@dadoonet](https://twitter.com/dadoonet)



 <https://david.pilato.fr/>





01

The bug



FScrawler

You know, for files!



github.com/dadoonet/fscrawler/

 Update Pull Requests files #525: Pull request #2059 synchronize by dadoonet	assertj	 3 months ago  1m 22s	
 Switch to AssertJ CodeQL #1388: Pull request #2059 synchronize by dadoonet	assertj	 3 months ago  5m 6s	
 Switch to AssertJ Build Pull Requests #1195: Pull request #2059 synchronize by dadoonet	assertj	 3 months ago  3m 58s	
 Switch to AssertJ CodeQL #1387: Pull request #2059 synchronize by dadoonet	assertj	 3 months ago  4m 53s	
 Switch to AssertJ Update Pull Requests files #524: Pull request #2059 synchronize by dadoonet	assertj	 3 months ago  1m 12s	
 Switch to AssertJ Update Pull Requests files #523: Pull request #2059 synchronize by dadoonet	assertj	 3 months ago  1m 10s	
 Switch to AssertJ	assertj	 3 months ago	

https://github.com/dadoonet/fscrawler/actions/runs/14357866984/job/40251514398#step:4:296

Summary

Jobs

- build
- unit**
- build-docker
- it
- it-es7
- it-es6
- it-cloud
- it-serverless

Run details

- Usage
- Workflow file

unit
failed 3 weeks ago in 38s

Search logs Explain error

Run all the unit tests 30s

```
340 Error:  
341 Error: To see the full stack trace of the errors, re-run Maven with the -e switch.  
342 Error: Re-run Maven using the -X switch to enable full debug logging.  
343 Error:  
344 Error: For more information about the errors and possible solutions, please read the following articles:  
345 Error: [Help 1] http://cwiki.apache.org/confluence/display/MAVEN/MojoExecutionException  
346 Error:  
347 Error: After correcting the problems, you can resume the build with the command  
348 Error: mvn <args> -rf :fscrawler-settings  
349 Error: Process completed with exit code 1.
```

Post Set up JDK 21 1s

Post Run actions/checkout@v4 0s

Complete job 0s

Throwable #1: `java.lang.NullPointerException`: Cannot invoke "`Elasticsearch.setIndex(String)`" because the return value of "`FsSettings.getElasticsearch()`" is `null`

Throwable #1: `java.lang.NullPointerException`: Cannot invoke "`Elasticsearch.setIndex(String)`" because the return value of "`FsSettings.getElasticsearch()`" is `null`

```
@Test
public void settingsValidation() {
    FsSettings settings = FsSettingsLoader.load();
    settings.getElasticsearch().setIndex(getCurrentTestName());

    // ...
}
```

```
@Test
public void settingsValidation() {
    FsSettings settings = FsSettingsLoader.load();
    settings.getElasticsearch().setIndex(getCurrentTestName());

    // ...
}
```



REPRODUCE WITH:

```
mvn integration-test -Dtests.locale=az
```

```
Throwable #1: java.lang.NullPointerException: Cannot invoke  
"Elasticsearch.setIndex(String)" because the return value of  
"FsSettings.getElasticsearch()" is null
```

It depends!





It depends!

```
@Test
public void settingsValidationFr() {
    Locale.setDefault(new Locale.Builder().setLanguageTag("fr").build());
    FsSettings settings = FsSettingsLoader.load();
    settings.getElasticsearch().setIndex(getCurrentTestName());

    // ...
}
```



```
@Test
public void settingsValidationAz() {
    Locale.setDefault(new Locale.Builder().setLanguageTag("az").build());
    FsSettings settings = FsSettingsLoader.load();
    settings.getElasticsearch().setIndex(getCurrentTestName());

    // ...
}
```

```
@Test
public void settingsValidationEn() {
    Locale.setDefault(new Locale.Builder().setLanguageTag("en").build());
    FsSettings settings = FsSettingsLoader.load();
    settings.getElasticsearch().setIndex(getCurrentTestName());
}
```

Randomized Testing





02

Installation

Installation (pom.xml - Java)

```
<dependency>  
  <groupId>com.carrotsearch.randomizedtesting</groupId>  
  <artifactId>randomizedtesting-runner</artifactId>  
  <version>2.8.3</version>  
  <scope>test</scope>  
</dependency>
```

Deactivate the default test plugin

```
<plugin>
  <groupId>org.apache.maven.plugins</groupId>
  <artifactId>maven-surefire-plugin</artifactId>
  <version>2.19</version>
  <executions>
    <execution>
      <id>default-test</id>
      <phase>none</phase>
    </execution>
  </executions>
</plugin>
```

Activate the randomized testing plugin

```
<plugin>  
  <groupId>com.carrotsearch.randomizedtesting</groupId>  
  <artifactId>junit4-maven-plugin</artifactId>  
  <version>2.8.3</version>  
  
  ...  
</plugin>
```



Configure the randomized testing plugin

```
...  
<executions>  
  <execution>  
    <id>unit-tests</id>  
    <phase>test</phase>  
    <goals>  
      <goal>junit4</goal>  
    </goals>  
  </execution>  
</executions>
```

Configure the randomized testing plugin

```
...
<configuration>
  <heartbeat>10</heartbeat>
  <jvmOutputAction>pipe,ignore</jvmOutputAction>
  <leaveTemporary>true</leaveTemporary>
  <ifNoTests>warn</ifNoTests>
  <listeners>
    <report-text showThrowable="true" showStackTraces="true" showOutput="always"
      showStatusOk="true" showStatusError="true"
      showStatusFailure="true" showStatusIgnored="true"
      showSuiteSummary="true" />
  </listeners>

  <systemProperties combine.children="append">
    <arg.common>arg.common</arg.common>
  </systemProperties>
</configuration>
...
```



03

Usage




```
@Test new *
public void testCreateClusterAndIndex() {
    int numberOfNodes = randomIntBetween(1, 20);
    int numberOfShards = randomIntBetween(1, 30);
    int numberOfReplicas = randomIntBetween(0, numberOfNodes - 1);
    String indexName = randomAsciiAlphanumOfLength(randomIntBetween(5, 20));


    // Create a cluster with the specified number of nodes
    startCluster(numberOfNodes);

    // Create an index with the specified number of shards and replicas
    createIndex(indexName, numberOfShards, numberOfReplicas);

    // Run tests here
    // ...
}
```

```
randomIntBetween(int min, int max) int
randomInt() int
randomInt(int max) int
randomAsciiAlphanumOfLength(int codeUnits) String
randomLongBetween(long min, long max) long
randomLong() long
randomLong(long max) long
randomBoolean() boolean
randomAsciiLettersOfLengthBetween(int minLetters, int maxLetters) String
randomAsciiLettersOfLength(int codeUnits) String
randomLocale() Locale
randomTimeZone() TimeZone
randomAsciiAlphanumOfLengthBetween(int minCodeUnits, int maxCodeUnits) String
randomByte() byte
randomBytesOfLength(int length) byte[]
randomBytesOfLength(int minLength, int maxLength) byte[]
randomDouble() double
randomFloat() float
randomFrom(int[] array) int
randomFrom(byte[] array) byte
randomFrom(char[] array) char
randomFrom(long[] array) long
```






04

Random

Spoiler: it's not really random



Seed



Seed

```
@Test
public void testSeed() {
    Random generator = new Random();
    int num = generator.nextInt();
    assertThat(num).isEqualTo(1553932502);
}
```

Seed

```
@Test
public void testSeed() {
    Random generator = new Random(12345L);
    int num = generator.nextInt();
    assertThat(num).isEqualTo(1553932502);
}
```



```
...
<configuration>
  <heartbeat>10</heartbeat>
  <jvmOutputAction>pipe,ignore</jvmOutputAction>
  <leaveTemporary>>true</leaveTemporary>
  <ifNoTests>warn</ifNoTests>
  <listeners>
    <report-text showThrowable="true" showStackTraces="true" showOutput="always"
      showStatusOk="true" showStatusError="true"
      showStatusFailure="true" showStatusIgnored="true"
      showSuiteSummary="true" />
  </listeners>
  <seed>${tests.seed}</seed>
  <systemProperties combine.children="append">
    <arg.common>arg.common</arg.common>
  </systemProperties>
</configuration>
...
```



REPRODUCE WITH:

```
mvn integration-test -Dtests.seed=489581FE40712E4A  
# -Dtests.locale=az -Dtests.timezone=Asia/Ashkhabad
```



REPRODUCE WITH:

```
mvn integration-test -Dtests.seed=489581FE40712E4A  
# -Dtests.locale=az -Dtests.timezone=Asia/Ashkhabad
```

```
@Test  
@Seed("489581FE40712E4A")  
public void settingsValidationForLocaleAz() {  
    // ...  
}
```

```

@Test @Repeat(iterations = 10)
public void repeatMe() {
    Locale locale = randomLocale();
    DateTimeFormatter dateTimeFormatter =
        DateTimeFormatter.ofLocalizedDate(FormatStyle.FULL).withLocale(locale);
    String format = dateTimeFormatter.format(LocalDate.now());
    System.out.println("date is [" + format + "] with locale [" +
        locale.toLanguageTag() + "]);
}

```



Run RandomTest.repeatMe



Stopped. 10 of 21 tests passed - 1s 443ms

Test Name	Duration	Status
repeatMe	1s 443ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:ABE85B69E20B2515]}	1s 66ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:1FBEE795D6C9EE39]}	52ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:91577149870DA6F2]}	31ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:A0B9DAACEBF3FDD8]}	35ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:EC785F014AFB3D60]}	18ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:7D828C5E37477060]}	18ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:435CE8D825776066]}	9ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:DFEF72A20663F4C8]}	56ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:ED4397CC71A8E392]}	91ms	OK
RandomTest.repeatMe { seed=[BDFFFF96C4FD53B5:3AC8C17615FFD4C0]}	67ms	OK

```

/Library/Java/JavaVirtualMachines/jdk1.8.0_60.jdk/Contents/Home/bin/java ...
date is [2016. o\u017cujka 11] with locale [hr]
date is [viernes 11 de marzo de 2016] with locale [es-CU]
date is [viernes 11 de marzo de 2016] with locale [es-US]
date is [11. mars 2016] with locale [no-NO]
date is [pi\u0105tek, 11 marca 2016] with locale [pl]
date is [11 2016 \u0645\u0627\u0631\u0627\u062a\u0627] with locale [ar-QA]
date is [Petek, 11. marec 2016] with locale [sl-SI]
date is [11 2016 \u0645\u0627\u0631\u0627\u062a] with locale [ar-BH]
date is [viernes 11 de marzo de 2016] with locale [es-CO]
date is [pi\u0105tek, 11 marca 2016] with locale [pl]

```

Process finished with exit code 0

```
<properties>
  <tests.locale>random</tests.locale>
</properties>
```

```
<configuration>
  ...
  <systemProperties combine.children="append">
    <arg.common>arg.common</arg.common>
    <tests.locale>${tests.locale}</tests.locale>
  </systemProperties>
</configuration>
```

```
private static final Locale savedLocale = Locale.getDefault();
```

```
@BeforeClass
```

```
public static void setLocale() {  
    String testLocale = System.getProperty("tests.locale", "random");  
    Locale locale = testLocale.equals("random") ? randomLocale() :  
        new Locale.Builder().setLanguageTag(testLocale).build();  
    Locale.setDefault(locale);  
}
```

```
@AfterClass
```

```
public static void resetLocale() {  
    Locale.setDefault(savedLocale);  
}
```

```
@Test
public void withLocale() {
    DateTimeFormatter dateTimeFormatter =
        DateTimeFormatter.ofLocalizedDate(FormatStyle.FULL);
    String format = dateTimeFormatter.format(LocalDate.now());
    System.out.println("locale = " + Locale.getDefault().toLanguageTag());
    System.out.println("format = " + format);
}
```

RUN 1

```
locale = es-PR
format = miércoles 9 de marzo de 2016
```

RUN 2

```
locale = tr-TR
format = 09 Mart 2016 Çarşamba
```

```
mvn test -Dtests.locale=fr-FR
```


```
1> locale = fr-FR
```

```
1> format = mercredi 9 mars 2016
```

```
@Test
public void sometimes() {
    int bulkSize = randomIntBetween(500, 1000);

    for (int i = 0; i < bulkSize; i++) {
        addDocument("english_" + i, generatePerson());
        if (frequently()) {
            addDocument("french_" + i, generatePerson());
        }

        if (rarely()) {
            // Shutdown Node 1
            shutdownNode(1);
        }
    }
}
```



05

But also



```
@Test
public void ignoreIfUseless() {
    boolean b = randomBoolean();

    assertThat(b).isTrue();
}
```

```
@Test
public void ignoreIfUseless() {
    boolean b = randomBoolean();

    assumeTrue(b);
    assertThat(b).isTrue();
}
```

RandomizedTest (fr.pilato.talk.randomizedtestin 7 ms

randomIntegerWithRange04

ignoreIfUseless20

7 ms

1 test ignored 1 test total, 7 ms

Process finished with exit code 0

(119) Starting test [ignoreIfUseless20]

(121) boolean is [false]

org.junit.AssumptionViolatedException: got: <false>, expected: is <true>

at __randomizedtesting.SeedInfo.seed([4A11AC3E62F994E2:6EC40FDC8D80D775]:0)

at org.junit.Assume.assumeThat(Assume.java:106)

at org.junit.Assume.assumeTrue(Assume.java:50)

at com.carrotsearch.randomizedtesting.RandomizedTest.assumeTrue(RandomizedTest.java:715)

```
@Test
public void ignoreIfUseless() {
    boolean b = randomBoolean();

    assumeTrue(b);
    assertThat(b).isTrue();
}
```

RandomizedTest (fr.pilato.talk.randomizedtesting) 26 ms 1 test passed 1 test total, 26 ms

- ✓ ignoreIfUseless20
- ✗ randomIntegerWithRange04

26 ms

```
/Users/david/.sdkman/candidates/java/21.0.2-open/bin/java ...
```

```
(57 ) 🌐 Starting test suite with Locale [ks-IN]
```

```
(119) 🎲 Starting test [ignoreIfUseless20]
```

```
(121) ➡ boolean is [true]
```

```
Process finished with exit code 0
```

Do less during the day

```
@Test @Nightly
public void longRunningTest() {
    int bulkSize = randomIntBetween(500, 1000);

    for (int i = 0; i < bulkSize; i++) {
        try {
            Thread.sleep(Math.abs(between(100, 10000)));
        } catch (InterruptedException e) {
            assumeNoException(e);
        }
    }
}
```

```
$ mvn test
```

```
IGNOR/A 0.00s | RandomTest.longRunningTest
> Assumption #1: 'nightly' test group is disabled (@Nightly(value=))
```

Do more during the night

```
<systemProperties combine.children="append">  
  <arg.common>arg.common</arg.common>  
  <tests.nightly>${tests.nightly}</tests.nightly>  
</systemProperties>
```

```
$ mvn test -Dtests.nightly=true
```

```
Started J0 PID(26908@MacBook-Pro-4.local).
```

```
Suite: fr.pilato.demo.testframework.RandomTest
```

```
HEARTBEAT J0 PID(26908@MacBook-Pro-4.local): 2016-03-10T18:04:19, stalled for 11.5s at:  
RandomTest.longRunningTest
```

```
HEARTBEAT J0 PID(26908@MacBook-Pro-4.local): 2016-03-10T18:04:29, stalled for 21.5s at:  
RandomTest.longRunningTest
```

```
HEARTBEAT J0 PID(26908@MacBook-Pro-4.local): 2016-03-10T18:04:39, stalled for 31.5s at:  
RandomTest.longRunningTest
```

```
HEARTBEAT J0 PID(26908@MacBook-Pro-4.local): 2016-03-10T18:04:49, stalled for 41.5s at:  
RandomTest.longRunningTest
```

```
OK      50.9s | RandomTest.longRunningTest
```

Do more during the night but stay reasonable

```
@Test @Nightly @Timeout(millis = 10000)
public void longRunningTest() {
    // ...
}
```

```
$ mvn test -Dtests.nightly=true
```

```
ERROR    10.0s | RandomTest.longRunningTest <<<
> Throwable #1: java.lang.Exception: Test timeout exceeded (>= 10000 msec).
>     at __randomizedtesting.SeedInfo.seed([F4FC818C113EF9C6:A3FC90C16C6643D6]:0)
```

ZOMBIE THREADS

```
@RunWith(RandomizedRunner.class)
```

```
public class RandomTest {  
    @Test  
    public void stopYourThreads() {  
        new Thread(() -> {  
            public void run() {  
                while (true) {  
                    try { Thread.sleep(1000L); } catch (InterruptedException e) { } }  
                } }, "zombie").start();  
        }  
    }  
}
```



ZOMBIE THREADS



```
@RunWith(RandomizedRunner.class)
```

```
public class RandomTest {  
    @Test  
    public void stopYourThreads() {  
        new Thread(() -> {  
            public void run() {  
                while (true) {  
                    try { Thread.sleep(1000L); } catch (InterruptedException e) { } }  
                } }, "zombie").start();  
        }  
    }  
}
```

com.carrotsearch.randomizedtesting.ThreadLeakError: **1 thread leaked** from SUITE scope at
fr.pilato.demo.testframework.RandomTest:

```
1) Thread[id=12, name=zombie, state=TIMED_WAITING, group=TGRP-RandomTest]  
   at java.lang.Thread.sleep(Native Method)  
   at fr.pilato.demo.testframework.RandomTest$1.run(RandomTest.java:180)  
   at java.lang.Thread.run(Thread.java:745)
```

```
at __randomizedtesting.SeedInfo.seed([1CD01D6C55CD93C0]:0)
```

ZOMBIE THREADS

```
@RunWith(RandomizedRunner.class)
@ThreadLeakFilters(filters = { FriendlyZombieFilter.class })
public class RandomTest {
    @Test
    public void identifyYourThreads() {
        new Thread(() -> {
            public void run() {
                while (true) {
                    try { Thread.sleep(1000L); } catch (InterruptedException e) { } }
                } }, "friendly-zombie").start();
    }
}


public class FriendlyZombieFilter implements ThreadFilter {
    public boolean reject(Thread t) {
        return "friendly-zombie".equals(t.getName());
    }
}
```



Random execution order

✓	RandomizedTest (fr.pilato.talk.randomizedtest)	48 ms
✓	randomWithSeed01	25 ms
✓	randomIntegerWithSeed03	1 ms
✓	stopOrIdentifyYourThreads30	2 ms
✓	randomLocale10	9 ms
✓	random00	2 ms
✓	ignoreIfUseless20	2 ms
✓	randomInteger02	1 ms
✓	randomIntegerWithRange04	6 ms
✓	RandomizedTest.randomIntegerWithRange	2 ms
✓	RandomizedTest.randomIntegerWithRange	2 ms
✓	RandomizedTest.randomIntegerWithRange	1 ms
✓	RandomizedTest.randomIntegerWithRange	1 ms
✓	RandomizedTest.randomIntegerWithRange	0 ms

✓	RandomizedTest (fr.pilato.talk.randomizedtest)	41 ms
✓	stopOrIdentifyYourThreads30	3 ms
✓	randomIntegerWithRange04	26 ms
✓	RandomizedTest.randomIntegerWithRange	22 ms
✓	RandomizedTest.randomIntegerWithRange	1 ms
✓	RandomizedTest.randomIntegerWithRange	1 ms
✓	RandomizedTest.randomIntegerWithRange	1 ms
✓	RandomizedTest.randomIntegerWithRange	1 ms
✓	ignoreIfUseless20	2 ms
✓	randomWithSeed01	1 ms
✓	randomIntegerWithSeed03	0 ms
✓	random00	0 ms
✓	randomInteger02	1 ms
✓	randomLocale10	8 ms



06

Back to the bug



```
@Test
public void settingsValidation() {
    FsSettings settings = FsSettingsLoader.load();
    settings.getElasticsearch().setIndex(getCurrentTestName());

    // ...
}
```



<https://github.com/gestalt-config/gestalt/issues/242>

```
@Test
public void testLocaleAz() throws Exception {
    Locale.setDefault(new Locale.Builder().setLanguageTag("az").build());
    Gestalt gestalt = new GestaltBuilder()
        .addSource(MapConfigSourceBuilder.builder()
            .addCustomConfig("elasticsearch.index", "foo")
            .build())
        .build();
    gestalt.loadConfigs();
    assertThat(gestalt.getConfigOptional("elasticsearch", Elasticsearch.class)).isPresent();
}
```

```
@Test
public void testLocaleFr() throws Exception {
    Locale.setDefault(new Locale.Builder().setLanguageTag("fr").build());
    Gestalt gestalt = new GestaltBuilder()
        .addSource(MapConfigSourceBuilder.builder()
            .addCustomConfig("elasticsearch.index", "foo")
            .build())
        .build();
    gestalt.loadConfigs();
    assertThat(gestalt.getConfigOptional("elasticsearch", Elasticsearch.class)).isPresent();
}
```

https://github.com/gestalt-config/gestalt/issues/242



credmond-git on Apr 11 · edited by credmond-git

Edits ▾ Collaborator ⋮

I found the root cause of the issue.

Gestalt uses the following pattern to tokenize a path.

```
pattern: ^((?<name>[\w .,+=\-\;:'"~!@#$$%^&*()\<>]+)(?<array>\[[(?<index>\d*)]?)?)$
```

When presented with the word: 'flushinterval'

the following doesn't find a match in the PathLexer: `Matcher matcher = pathPattern.matcher(word);`

It seems to work in every other Locale, but Az?

I need to look into why this is happening, and how to fix it.



credmond-git mentioned this on Apr 11

[🔗 fix: specify the root locale when using toLower. #243](#)




credmond-git on Apr 11

Collab

I also made a fix so we can support different languages Unicode characters for object field names. [#244](#)




```
@Test(expected = NullPointerException.class)
@Seed("489581FE40712E4A")
public void testGestalt242() throws Exception {
    FsSettings settings = FsSettingsLoader.load();
    // This is supposed to fail because of:
    // https://github.com/gestalt-config/gestalt/issues/242
    settings.getElasticsearch().setIndex(getCurrentTestName());
    fail("The Gestalt project probably fixed issue 242");
}
```



07

Limitations







Thanks!

Do you have any questions?

David Pilato



 [linkedin.com/in/dadoonet/](https://www.linkedin.com/in/dadoonet/)



Slides

<https://speaker.pilato.fr/6DyIt6>

 **Testµ 2025**
BY LAMBDATEST